



HHXX.EX6624
Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze

Page Bottom

Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze

See General Information for Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze

JINAN MEIDE CASTING CO LTD

EX6624

3 NANMEN RD

PINGYIN

JINAN, SHANDONG 250400 CHINA

Ductile Iron Fittings (ANSI/ASME B16.3)

Fittings fabricated with dimensional specifications in accordance with ANSI/ASME B16.3

Model	Configuration	Size, in.	Rated Pressure, psig
90	90° Elbow	1/2, 3/4, 1,	500
		1-1/4, 1-1/2, 2, 2-1/2,	
		3, 4	
90R	Reducing 90° Elbow	3/4 x 1/2	500
		1 x 1/2, 3/4	
		1-1/4 x 1/2, 3/4, 1	
		1-1/2 x 1/2, 3/4, 1, 1-1/4;	
		2 x 1/2, 3/4, 1, 1-1/4, 1-1/2	
		2-1/2 x 1-1/2, 2	
		3 x 3/4	
120	45° Elbow	1/2, 3/4, 1,	500
		1-1/4, 1-1/2, 2, 2-1/2	
130	Tee	1/2, 3/4, 1,	500
		1-1/4, 1-1/2, 2, 2-1/2,	
		3, 4	
130R	Reducing Tee	3/4 x 3/4 x 1/2, 1	500
		3/4 x 1/2 x 1/2, 3/4	
		1 x 1/2 x 1	
		1 x 3/4 x 3/4, 1	
		1 x 1 x 1/2, 3/4, 1-1/4, 1-1/2	
		1-1/4 x 1/2 x 1-1/4	
		1-1/4 x 3/4 x 1-1/4	
		1-1/4 x 1 x 1/2, 3/4, 1, 1-1/2, 1-1/4	
		1-1/4 x 1-1/4 x 1/2, 3/4, 1, 1-1/2, 2	
		1-1/2 x 1/2 x 1-1/4, 1-1/2	

		1-1/2 x 3/4 x 1-1/4, 1-1/2	
		1-1/2 x 1 x 1/2, 3/4, 1, 1-1/4, 1-1/2	
		1-1/2 x 1-1/4 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 1, 2	
		1-1/2 x 1-1/2 x 1/2, 3/4, 1, 1-1/4, 2	
		2 x 1 x 2	
		2 x 1-1/4 x 2	
		2 x 1-1/2 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2	
		2 x 2 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2-1/2	
		2-1/2 x 2-1/2 x 3/4, 1, 1-1/4, 1-1/2, 2, 3	
241	Hex Bushing	1, 1-1/4, 1-1/2, 2, 1-1/4x3/4	500
220	Straight Coupling w/stop	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	500
240	Reducing Coupling w/hex	1 x 1/2, 3/4 1-1/4 x 3/4, 1 1-1/2 x 1, 1-1/4 2 x 1, 1-1/4, 1-1/2	500
180	Cross	1, 1-1/4, 1-1/2, 2 3/4	500
180R	Reducing Cross	1-1/4 x 1 1-1/2 x 1 2 x 1	500
300	Cap	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	500
291	Square Head Plug	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
342	Union	1, 1-1/4, 1-1/2, 2	500

CAST IRON FITTINGS

Cast Iron Fittings (ANSI/ASME B16.4)

Model	Configuration	Size, in.	Rated Pressure, psig
90	90° Elbow	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
90R	Reducing 90° Elbow	3/4 x 1/2 1 x 1/2, 3/4 1-1/4 x 1/2, 3/4, 1 1-1/2 x 1/2, 3/4, 1, 1-1/4 2 x 1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2 x 3/4, 1, 1-1/4, 1-1/2, 2 3 x 2 3/4x1/2, 3x2	300

120	45° Elbow	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
130	Tee	1, 1-1/4, 1-1/2, 2, 2-1/2 3, 4	300
130R	Reducing Tee	1x1x1-1/2, 2x1/2x2, 2x1x1-1/2, 2-1/2x1/2x2-1/2, 2-1/2x2x1/2, 2-1/2x2x3/4, 2-1/2x2x1, 2-1/2x2x1-1/4, 2-1/2x2x1-1/2, 2-1/2x2x2, 2-1/2x2x2-1/2, 3x3x1-1/4, 3x3x1-1/2, 3x3x2	300
180	Cross	1, 1-1/4, 1-1/2, 2	300
180R	Reducing Cross	1-1/4 x 1 1-1/2 x 1 2 x 1	300
240	Reducing Coupling w/hex	1 x 1/2, 3/4 1-1/4 x 1 2 x 3/4, 1	300
291	Cored Plugs	3/4, 1, 1-1/4, 1-1/2, 2	300
291S	Solid Plugs	1/2	300

Malleable Iron Fittings (ANSI/ASME B16.3, ANSI/ASME B16.14)

Fittings fabricated with dimensional specifications in accordance with ANSI/ASME B16.3

Model	Configuration	Size, in.	Rated Pressure, psig
90	90° Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
90	90° Elbow	2-1/2, 3, 3-1/2, 4, 5, 6	300
90R	90° Reducing Elbow	1/2x1/4, 3/8; 3/4x1/4, 3/8, 1/2; 1x3/8, 1/2, 3/4; 1-1/4x1/2, 3/4, 1; 1-1/2x3/4, 1, 1-1/4; 2x3/4, 1, 1-1/4, 1-1/2	500
90R	90° Reducing Elbow	2-1/2x1-1/2, 2; 3x2, 2-1/2; 4x3	300
92	90° Street Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
92	90° Street Elbow	2-1/2, 3, 4, 6	300
120	45° Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
120	45° Elbow	2-1/2, 3, 4, 5, 6	300
121	45° Street Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
121	45° Street Elbow	2-1/2, 3, 4	300
130	Tee	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
130	Tee	2-1/2, 3, 3-1/2, 4, 5, 6	300
130R	Reducing Tee	3/8x3/8x1/2, 1/2x1/4x1/2, 1/2x3/8x1/2, 1/2x1/2x1/4, 1/2x1/2x3/8, 1/2x1/2x3/4, 1/2x1/2x1, 3/4x1/2x1/2, 3/4x1/2x3/4, 3/4x3/4x1/4, 3/4x3/4x3/8, 3/4x3/4x1/2, 3/4x3/4x1, 1x1/2x1/2, 1x1/2x3/4, 1x1/2x1, 1x3/4x1/2, 1x3/4x3/4, 1x3/4x1, 1x1x1/4, 1x1x3/8, 1x1x1/2, 1x1x3/4, 1x1x1-1/4, 1x1x1-1/2, 1x1x2, 1-1/4x1/2x1, 1-1/4x1/2x1-1/4, 1-1/4x3/4x3/4, 1-1/4x3/4x1, 1-1/4x3/4x1, 1-1/4x3/4x1-1/4, 1-1/4x1x1/2, 1-1/4x1x3/4, 1-1/4x1x1, 1-1/4x1x1-1/4, 1-1/4x1-1/4x3/8, 1-1/4x1-1/4x1/2, 1-1/4x1-1/4x3/4, 1-1/4x1-1/4x1, 1-1/4x1-1/4x1-1/2, 1-1/4x1-1/4x2, 1-1/2x1 /2x1-1/2, 1-1/2x3/4x1-1/2, 1-1/2x1x1, 1-1/2x1x1-1/4, 1-1/2x1x1-1/2, 1-1/2x1-1 /4x1/2, 1-1/2x1-1/4x3/4, 1-1/2x1-1/4x1, 1-1/2x1-1/4x1-1/4, 1-1/2x1-1/4x1-1/2, 1-1/2x1-1/2x1/2, 1-1/2x1-1/2x3/4, 1-1/2x1-1/2x1, 1-1/2x1-1/2x1-1/4, 1-1/2x1-1/2x2, 2x1/2x2, 2x3/4x2, 2x1x1-1/2, 2x1x2, 2x1-1/4x1-1/4, 2x1-1/4x1-1/2, 2x1-1/4x2, 2x1-1/2x1, 2x1-1/2x1-1/4, 2x1-1/2x1-1/2, 2x1-1/2x2, 2x2x1/2, 2x2x3/4,	500

		2x2x1, 2x2x1-1/4, 2x2x1-1/2	
130R	Reducing Tee	2x2x2-1/2, 2-1/2x1-1/2x2, 2-1/2x1-1/2x2-1/2, 2-1/2x2x2, 2-1/2x2x2-1/2, 2-1/2x2-1/2x3/4, 2-1/2x2-1/2x1, 2-1/2x2-1/2x1-1/4, 2-1/2x2-1/2x1-1/2, 2-1/2x2-1/2x2, 3x2x2, 3x2x3, 3x3x3/4, 3x3x1, 3x3x1-1/4, 3x3x1-1/2, 3x3x2, 3x3x2-1/2, 4x4x1-1/2, 4x4x2, 4x4x2-1/2, 4x4x3	300
134	Street Tee	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
165	45° Y-Branches	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
165	45° Y-Branches	2-1/2, 3, 4	300
180	Cross	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
180	Cross	2-1/2, 3, 3-1/2, 4	300
180R	Reducing Cross	3/4x1/2, 1x1/2, 1x3/4, 1-1/4x3/4, 1-1/4x1, 1-1/2x3/4, 1-1/2x1, 1-1/2x1-1/4, 2x3/4, 2x1, 2x1-1/4, 2x1-1/2	500
180R	Reducing Cross	2-1/2x2, 3x2	300
220	Coupling	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
220	Coupling	2-1/2, 3, 4	300
240	Reducing Coupling	1/2x1/8, 1/2x1/4, 1/2x3/8, 3/4x1/4, 3/4x3/8, 3/4x1/2, 1x1/4, 1x3/8, 1x1/2, 1x3/4, 1-1/4x1/2, 1-1/4x3/4, 1-1/4x1, 1-1/2x1/2, 1-1/2x3/4, 1-1/2x1, 1-1/2x1-1/4, 2x1/2, 2x3/4, 2x1, 2x1-1/4, 2x1-1/2	500
240	Reducing Coupling	2-1/2x1-1/2, 2-1/2x2, 3x1-1/2, 3x2, 3x2-1/2, 4x2, 4x3	300
300	Cap	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
300	Cap	2-1/2, 3, 3-1/2, 4, 5, 6	300

Fittings fabricated with dimensional specifications in accordance with ANSI/ASME B16.14

Model	Configuration	Size, in.	Rated Pressure, psig
241	Bushing	1/2x1/8, 1/2x1/4, 1/2x3/8, 3/4x1/8, 3/4x1/4, 3/4x3/8, 3/4x1/2, 1x1/8, 1x1/4, 1x3/8, 1x1/2, 1x3/4, 1-1/4x1/4, 1-1/4x3/8, 1-1/4x1/2, 1-1/4x3/4, 1-1/4x1, 1-1/2x1/4, 1-1/2x3/8, 1-1/2x1/2, 1-1/2x3/4, 1-1/2x1, 1-1/2x1-1/4, 2x1/4, 2x3/8, 2x1/2, 2x3/4, 2x1, 2x1-1/4, 2x1-1/2, 2-1/2x1/2, 2-1/2x3/4, 2-1/2x1, 2-1/2x1-1/4, 2-1/2x1-1/2, 2-1/2x2, 3x1/2, 3x3/4, 3x1, 3x1-1/4, 3x1-1/2, 3x2, 3x2-1/2, 3-1/2x2-1/2, 3-1/2x3, 4x1-1/4, 4x1-1/2, 4x3, 4x3-1/2, 5x4, 6x5	300
291	Cored Plugs	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 3-1/2	300
291S	Solid Plugs	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 3-1/2	300
291-4	Slotted Head Plugs	4, 5, 6	300
291N	Countersunk Plugs	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300

Malleable Iron Fittings, ISO 49/EN 10242 (threads manufactured in accordance with ISO 7-1):

Model	Configuration	Size, in.	Rated Pressure, psig
1#	Bend 90 degree, male and female	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 6"	500
1A	Short Bend 90 degree, male and female	1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2"	500
2#	Bend 90 degree, female	1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4"	500

2A	Short Bend 90 degree, female	1/2",3/4",1",1-1/4",1-1/2",2"	500
3#	Bend 90 degree, male	3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4"	500
40	Bend 45 degree, male and female	1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4",6"	500
41	Bend 45 degree, female	1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4"	500
85	Crossover	1/2",3/4",1",1-1/4",1-1/2",2"	500
90	Elbow, 90 degree	1/8",1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4",6", 5"	500
90R	Elbow, 90 degree, reducing	3/8"x1/4",1/2x3/8",3/4x3/8",3/4x1/2",1x1/2",1x3/4",1-1/4x3/4",1-1/4x1",1x1/4",1x3/8",1x1/2",1x3/4",1-1/4x3/8", 1-1/4x1/2", 1-1/4x3/4", 1-1/4x1",1-1/2x1/2",1-1/2x3/4",1/4x1/8",3/8x1/8",1/2x1/4",3/4x1/4",1x1/4",1x3/8",1-1/4x3/8",1-1/4x1/2",1-1/2x1/2",1-1/2x3/4",2x1/2",2x3/4",2x1",2x1-1/4",2-1/2x1/2",2-1/2x3/4",2-1/2x1",2-1/2x1-1/4",2-1/2x1-1/2",3x3/4",3x1",3x1-1/4",3x1-1/2",3x2-1/2",4x1",4x1-1/4",4x1-1/2",4x2",4x2-1/2",4x3",6x4 11/2x1", 11/2x11/4", 2x11/2", 21/2x2"	500
92	Stree Elbow, 90 degree	1/8",1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4",6"	500
92R	Stree Elbow, 90 degree, reducing	3/4"x1/2",1"x3/4"	500
95	Union elbow, F&F, Flat seat without gasket	1/2",3/4",1,1-1/4",1-1/2",2"	500
96	Union elbow, F&F, conical joint iron to iron	1/4",3/8",1/2",3/4",1,1-1/4",1-1/2",2"	500
97	Union elbow, M&F, Flat seat without gasket	11/2"	500
98	Union elbow, M&F, conical joint iron to iron	1/2",3/4",1,1-1/4",1-1/2",2"	500
120	Elbow, 45 degree	1/8",1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4",5,6"	500
121	Stree Elbow, 45 degree	1/8",1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2, 2-1/2",3,4"	500
130	Tee	1/8",1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4",5,6"	500
130R	Tee, reducing	3/8x1/4,1/2x1/4,1/2x3/8,3/4x1/4, 3/4x3/8,3/4x1/2,1x1/4,1x3/8, 1x1/2,1x3/4,1-1/4x3/8,1-1/4x1/2, 1-1/4x3/4,1-1/4x1,1-1/2x1/2,1-1/2x3/4,1-1/2x1, 1-1/2x1-1/4,2x1/2,2x3/4,2x1, 2x1-1/4,2x1-1/2,2-1/2x1,2-1/2x1-1/4,2-1/2x1-1/2, 2-1/2x2,3x1,3x1-1/4,3x1-1/2,3x2,3x2-1/2,4x2,4x3,1/4x1/8,1/2x1/8,1-1/2x3/8,2x3/8,2-1/2x1/2,2-1/2x3/4,3x1/2,3x3/4, 4x1/2,4x3/4,4x1,4x1-1/4,4x1-1/2,4x2-1/2,6x2,6x3,6x4, 1/2x1/2x3/4,1/2x1/2x1,3/4x3/4x1, 3/4x3/4x1-1/4,1x1x1-1/4,1x1x1-1/2,1x1x2,1x1x2-1/2,1-1/4x1-1/4x1-1/2,1-1/4x1-1/4x2,1-1/2x1-1/2x2,1-1/2x1-1/2x2-1/2,2x2x2-1/2,2-1/2x2-1/2x3,2-1/2x2-1/2x4, 3/4x1/2x1/2,1x1/2x1/2,1x3/4x3/4, 1-1/4x1/2x1/2,1-1/4x3/4x3/4,1-1/4x1x1,1-1/2x3/4x3/4,1-1/2x1x1,1-1/2x1-1/4x1-1/4,2x1x1,2x1-1/4x1-1/4,2x1-1/2x1-1/2,2x1-1/2x1-1/2,2-1/2x2,3x2x2,3/4x1/2x3/4,1x1/2x1,1x3/4x1,1x1/4x1,1-1/4x1/2x1-1/4,1-1/4x3/4x1-1/4,1-1/4x1x1-1/4,1-1/2x1/2x1-1/2,1-1/2x3/4x1-1/2,1-1/2x1x1-1/2,1-1/2x1-1/4x1-1/2,2x1/2x2,2x3/4x2,2x1x2, 2x1-1/4x2,2x1-1/2x2,2-1/2x1-1/2x2-1/2,2-1/2x2x2-1/2,3/4x1/2x1,1x1/2x3/4,1x3/4x1/2,	500

		1-1/4x1/2x3/4,1-1/4x1/2x1,1-1/4x3/4x1/2,1-1/4x3/4x1,1-1/4x1x1/2,1-1/4x1x3/4,1-1/2x3/4x1,1-1/2x3/4x1-1/4,1-1/2x1x1/2,1-1/2x1x1-1/4,1-1/2x1-1/4x1/2,1-1/2x1-1/4x3/4,1-1/2x1-1/4x1,	
		1-1/2x1-1/4x2,2x1x1-1/2,2x1-1/4x1,2x1-1/4x1-1/2,2x1-1/2x1/2,2x1-1/2x3/4,2x1-1/2x1,2x1-1/2x1-1/4,2-1/2x2x1/2,2-1/2x2x1,2-1/2x2x1-1/4	
131	Pitcher Tee, equal 90 degree	1/2,3/4,1,1-1/4,1-1/2, 2"	500
134	Service Tee, equal	1/4",1/2,3/4,1,1-1/4,1-1/2, 2"	500
134R	Service Tee, Reducing	2"x11/2",2-1/2x2,3x21/2"	500
165	Lateral Y branch, 45 degree	1/2",3/4",1",1-1/4",1-1/2",2", 2-1/2",3",4	500
180	Cross	1/8",1/4,1/2",3/4",1",1-1/4",1-1/2",2", 2-1/2",3",4", 3/8"	500
180R	Cross, reducing	3/4"x1/2",1x1/2,1x3/4,1-1/4x3/4, 1-1/4x1,11/2"x1",11/4"x1/2",1-1/2x1/2,1-1/2x3/4,1-1/2x1-1/4,2x3/4,2x1,2x1-1/4, 2x1-1/2,21/2"x1",21/2"x11/4",21/2"x11/2",21/2"x2",3x3/4,3x1,3x1-1/4,3x1-1/2,3"x2",3"x21/2",4x1,4x1-1/4,4x1-1/2, 4x2,4x2-1/2,4"x3"	500
220	Socket/Coupling	1/8",1/4",3/8",1/2",3/4",1",1-1/4",1-1/2",2",2-1/2",3",4",5,6"	500
240	Socket/Coupling, reducing	1/4"x1/8",3/8x1/8,3/8x1/4,1/2x1/4, 1/2x3/8,3/4x1/4,3/4x3/8,3/4x1/2, 1x3/8,1x1/2,1"x3/4",11/4"x1/2",1-1/4x3/4,1-1/4x1,1-1/2x1/2, 1-1/2x3/4,1-1/2x1,1-1/2x1-1/4, 2x1/2,2x3/4,2x1,2x1-1/4,2"x11/2",21/2"x11/4",21/2"x11/2,21/2"x2, 3x1-1/2,3x2,3"x21/2",1/2"x1/8",3/4"x1/8",1x1/4,1-1/4x1/4, 1-1/4x3/8,1-1/2x1/4,1-1/2x3/8,2-1/2x1/2, 2-1/2x3/4,2-1/2x1,3x1/2,3x3/4,3x1, 3"x11/4"	500
241	Bushing(241)	1/4"x1/8",3/8x1/8,3/8x1/4,1/2x1/8, 1/2x1/4,1/2x3/8,3/4x1/8,3/4x1/4, 3/4x3/8,3/4x1/2,1x1/8,1x1/4,1"x3/8",1x1/2,1x3/4,1-1/4x1/4,1-1/4x3/8,1-1/4x1/2,1-1/4x3/4,1-1/4x1,1-1/2"x1/4",1-1/2"x3/8", 1-1/2"x1/2",21/2"x11/2",2-1/2x2,3x1/2, 3x3/4,3x2,3"x21/2",11/2"x3/4",1-1/2x1,1-1/2x1-1/4, 2x1/4,2x3/8,2x1,2x1-1/4,2x1-1/2,2-1/2x1/2,21/2"x3/4",31/2"x3",4x3/4,4x1,4x1-1/4, 4x1-1/2,4x3,5x3,5x4, 6x2,6x2-1/2,6x5	500
241D	Bushing(241D)	2"x1/2",2x3/4,2-1/2x1,2-1/2x1-1/4, 3x1,3x1-1/4,3x1-1/2,4x2, 4x2-1/2,6x3,6x4	500
245	Hexagon Nipple, reducing	3/8"x1/4",1/2x1/4,1/2x3/8,	500

		3/4x3/8,3/4x1/2,1x1/2,1x3/4, 1-1/4x1/2,1-1/4x3/4,1 1/4"X1",1 1/2"X3/4",1-1/2x1,1-1/2x1-1/4, 2x1,2x1-1/4,2x1-1/2,2-1/2x2, 3x2,3"X2 1/2",1/4"X1/8",3/4x1/4,1-1/2x1/2, 2x1/2,2x3/4,2-1/2x1,2-1/2x1-1/4, 2-1/2x1-1/2,3x1-1/2,4x2,4x2-1/2, 4"X3"	
246	Extension piece, sockets M&F, reducing	3/8"X1/4",1/2x1/4,1/2x3/8,3/4x3/8, 3/4x1/2,1x1/2,1x3/4,1-1/4x1/2, 1-1/4x3/4,1-1/4x1,1-1/2x3/4,1-1/2x1, 1-1/2x1-1/4,2x1,2x1-1/4,2"X1 1/2"	500
270	Socket, parallel threads, equal	1/8",1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4",6"	500
271	Socket, right & left threads	1/2",3/4",1,1-1/4,1-1/2,2"	500
280	Hexagon Nipple, equal	1/8",1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4",5",6"	500
291	Plug	1/8",1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4",6"	500
291N	Countersunk Plug	1/2,3/4",1",1-1/4", 1-1/2",2",2-1/2",3"	500
291S	Solid Plug	1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4"	500
300	Cap	1/8",1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4",5,6"	500
310	Locknut	1/4",3/8",1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4"	500
312	Backnut	1/2",3/4",1",1-1/4", 1-1/2",2",4"	500
321-4	Flange(321-4)	1-1/4", 1-1/2",2",2-1/2",3",4",6"	500
321-6	Flange(321-6)	1-1/4", 1-1/2",2",2-1/2",3",4",6"	500
321H	Flange(321H)	1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4"	500
321N	Flange(321N)	2"	500
321P	Flange, DRP D	1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4",5,6"	500
321PW	Flange, U/D	1/2",3/4",1",1-1/4", 1-1/2",2",2-1/2",3",4",5,6"	500

321TD	Flange, BS Table D	1",1-1/4",	500
		1-1/2",2",2-1/2",3",4",6"	
321W	Flange, without bolt hole	1/2",3/4",1",1-1/4",	500
		1-1/2",2",2-1/2",3",4	
526	Extension Tube	1/2"X30,1/2"X40,1/2"X50,1/2"X60,	500
		1/2"X100	
529A	Extention Long piece	1/2",3/4",1",1-1/4",	500
		1-1/2",2"	
529X	Extention Short piece	1/2"	500
1090	Elbow, 90 degree, plain	1/2",1-1/4",2"	500
1130	Tee, plain	1/2",1",1-1/4",	500
		1-1/2"	
1220	Socket, plain, with ribs	1/2",3/4",1",1-1/4",	500
		1-1/2",2",2-1/2",3"	
1221	Side outlet elbow	1/2",3/4",1",1-1/4",	500
		1-1/2",2"	
1223	Side outlet tee	1/2",3/4",1"	500

Last Updated on 2012-05-23

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".